

An interior primer designed to penetrate and seal new wood surfaces. Dries to a hard sandable finish and produces excellent enamel hold-out characteristics.

**1. RECOMMENDED USES:** Use on new wood or plaster. May also be used for repainting old painted porous surfaces.

**2. LIMITATIONS:** Do not paint over chalk, dust, dirt, grease, mildew, rusty or glossy surfaces. For interior use only. Apply only when the atmospheric temperature and surface temperature will remain above 50°F, and not in foggy or rainy weather.

**3. RECOMMENDED FINISHES:**

50 Wallkyd Flat Oil, 300 Alkyd Semi-gloss, 400 Acrylic Semi-gloss, 600 Velvet Flat, 860 Imflo Alkyd Gloss, A4400 Acrylic Low-luster, 3500 Interior Flat, 4500 Interior Flat, 5500 Professional Flat, 1300 Acrylic Epoxy, 8600 Acrylic Waterborne Enamel Gloss.

**4. COLOR:** White

**5. TECHNICAL DATA:**

**Drying Time:** ..... @ 77°F and 50% RH  
3-4 hrs. - TO THE TOUCH  
24 hrs - TO RECOAT

**Finish:** ..... Flat

**Coverage:** ..... 472 SQ. Ft. @ 1.7 MIL DFT

**Viscosity:** ..... 90-95 KU

**Vehicle Type:** ..... Alkyd

**Solids By Volume:** ..... 50.04 ± 2.0%

**Weight Per Gallon:** ..... 11.73 LB ± 2.0%

**Flash Point:** ..... 108°F

**VOC:** ..... 372 g/l

**6. SURFACE PREPARATION:** Surface must be dry and free of chalk, dirt, grease, oil and mildew.

**7. MIXING:** One component. Stir thoroughly in a lifting motion before using.

**8. THINNING:** Mineral spirits if necessary.

**9. SHELF LIFE:** 12 Months.

**10. CLEAN-UP:** Mineral spirits

**11. CAUTION:** Vapor harmful. May affect brain or nervous system causing dizziness, headache or nausea. Causes nose and throat irritation.

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **DO NOT TAKE INTERNALLY.** In case of spillage, absorb and dispose of according to local and federal regulations. **KEEP OUT OF REACH OF CHILDREN.**

**KEEP AWAY FROM HEAT AND FLAME.** Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Use (NIOSH/MSHA TC 23C or EQUIVALENT) respirators.

**FIRST AID:** IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. **IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.**

**NOTE:** ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.

**ROSE  
TALBERT  
PAINT COMPANY**

**P.O. BOX 2658  
CAYCE-WEST COLUMBIA, S.C. 29171  
803-796-0324**