

Clean 5000 is a premium quality flat finish made with a durable vinyl acrylic emulsion that forms a smooth, uniform, & dirt resistant finish. It has excellent hiding, uniform touch-up, and washing characteristics. Clean 5000 Products are zero VOC and low odor formulations.

1. RECOMMENDED USES: To be used as a finish coat on drywall, plaster, concrete block, masonry, wood, and steel.

2. LIMITATIONS: Do not paint over chalk, dust, dirt, grease, mildew, rusty or glossy surfaces. For interior use only. Apply only when the atmospheric temperature and surface temperature will remain above 50°F, and not in foggy or rainy weather. Do not wash with hard or abrasive cleaners. Use a mild detergent, warm soapy water and soft cloth to remove dirt.

3. RECOMMENDED FINISHES:

- A. Drywall: 690 Premium Vinyl Emulsion Primer; Clean 5690 Premium Vinyl Emulsion Primer; 250 Bondaplex Interior/Exterior Primer.
- B. Plaster: 180 Premium Enamel Undercoat (Alkyd); 690 Premium Vinyl Emulsion Primer; Clean 5690 Vinyl Emulsion Primer.
- C. Wood: 250 Bondaplex Acrylic Primer; 180 Premium Enamel Undercoat (Alkyd); 690 Premium Vinyl Emulsion Primer; Clean 5690 Premium Vinyl Emulsion Primer.
- D. Masonry: 690 Premium Vinyl Emulsion Primer; Clean 5690 Premium Vinyl Emulsion Primer; 250 Bondaplex Interior/Exterior Primer.
- E. Concrete Block: 3550 HD Block Filler/ 650 Block Filler; 5550 Heavy Duty Vinyl Block Filler Zero VOC.
- F. Steel: #76 Zinc Chromate Metal Primer; 78 White Metal Primer; 9072 High Solids Phenolic Gray Primer; 9074- 66 High Solids Phenolic Red Oxide Primers; 8900 Aqua Chem DTM Primer/Finish.
- G. Aluminum: #76 Zinc Chromate Metal Primer; 8900 Aqua Chem DTM Primer/Finish.
- H. Galvanized: No primer necessary..

4. COLOR: 1400 Custom colors

5. TECHNICAL DATA:

Drying Time:..... @ 77°F
30 mins. - TO THE TOUCH
2-4 hr - TO RECOAT
Finish:..... Flat

Coverage:584 SQ. Ft. @ 1.0 MIL DFT
Viscosity: 95-100 KU
Vehicle Type:..... Vinyl Acrylic
Solids By Volume: 36.4 ± 2.0%
Weight Per Gallon: 11.54 LB ± 2.0%
Flash Point:..... N/A°F
VOC: 0 g/l

6. SURFACE PREPARATION: Surface must be dry and free of chalk, dirt, grease, oil and mildew.

7. MIXING: One component. Stir thoroughly in a lifting motion before using.

8. THINNING: Water if necessary.

9. SHELF LIFE: 12 Months

10. CLEAN-UP: Warm soapy water.

11. CAUTION: PROTECT FROM FREEZING: VAPOR MAY BE HARMFUL. BREATHING OF VAPOR MAY CAUSE RESPIRATORY IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. CAUSES EYE IRRITATION. DO NOT TAKE INTERNALLY. IN CASE OF SPILLAGE ABSORB AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. **IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.**

NOTE: ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.



**P.O. BOX 2658
CAYCE-WEST COLUMBIA, S.C. 29171
803-796-0324**